

SDS Number: 15005 Revision Date: June 24, 2024



HMIS	
Health Hazard	0
Fire Hazard	1
Reactivity	0

This SDS Is in accordance with US 2012 OSHA Hazard Communication Standard (29 CFR1910.1200) or the Canadian Workplace Hazardous Material Information System (WHMIS 2015)

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name TRIAX Agra Supreme 15W-40

Recommended Use Synthetic Diesel Engine Oil

Manufactured by: TRIAX LLC

1405 S Belt Line RD, Suite 200, Coppell, TX 75019

Phone: 214-897-6533

Emergency Telephone Number CHEMTREC

1 (800) 424-9300

International: +011(703) 527-3887

2. HAZARDS IDENTIFICATION

Emergency Overview

Classification

This product is **not considered hazardous** by either the US 2012 OSHA Hazard Communication Standard (29 CFR1910.1200) or the Canadian Workplace Hazardous Material Information System (WHMIS 2015.

Appearance Clear light yellow Physical State liquid Odor Petroleum odor

liquid

Potential Health Effects

Acute Toxicity

EyesNo significant effects or critical hazards.SkinNo significant effects or critical hazards.InhalationNo significant effects or critical hazards.IngestionNo significant effects or critical hazards.

Environmental Hazard See Section 12 for additional Ecological Information.

Other hazards None known



SDS Number: 15005 Revision Date: June 24, 2024

3. COMPOSITION / INFORMATION ON INGREDIENTS

Formula Mixture

Chemical Name	CAS-No	Weight %
Lubricant Base Oil (Petroleum) Highly	Mixture of Group III and PAO	80-90%
refined synthetic oils (C15-C50)	Polyalphaol	
Engine Oil Additive Mixture	Proprietary and Confidential*	10-20%
Anti-Wear additive mixture	Proprietary and Confidential*	5-10%

This product does not contain known hazardous materials at the \geq 1% level or known carcinogens at the \geq 0.1% level as defined by 29 CFR 1910.1200.

4. FIRST-AID MEASURES

Eye Contact Flush with large amounts of water for 15 minutes.

Skin Contact Wash off immediately with soap and plenty of water for at least 15 minutes while removing

all contaminated clothing and shoes.

Inhalation This material is not expected to present an inhalation exposure at ambient conditions.

Ingestion Never give anything by mouth to an unconscious person. Do not induce vomiting. Get

immediate medical attention or advice.

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties NOT FLAMMABLE

Flash Point >400 °F

Suitable Extinguishing Media Water fog, Foam, CO₂, dry chemical

Unsuitable Extinguishing Media Not Available

Hazardous Combustion Products Not Available

Explosion Data

Sensitivity to Mechanical Impact
Sensitivity to Static Discharge
Not sensitive
Not sensitive

Protective Equipment and Precautions for

Firefighters

Wear positive pressure self-contained breathing apparatus (SCBA). Use water to cool containers exposed to flames. Structural firefighters' protective clothing will only provide limited protection. Mist or sprays may be flammable below the product normal

flash point.

^{*} Exact % of composition is being withheld as a trade secret.



SDS Number: 15005 Revision Date: June 24, 2024

NFPA Health Hazard 0 Flammability 1 Stability 0 Physical and Chemical Hazards

6. ACCIDENTAL RELEASE MEASURES

Personal PrecautionsUse personal protective equipment. Avoid contact with skin, eyes, and clothing.

Ensure adequate ventilation. If spilled, take caution, as material can cause surfaces

to become very slippery.

Methods for Containment Dike far ahead of liquid spill for later disposal.

Methods for Cleaning Up Pick up free liquid for recycle and/or disposal. Residual liquid and/or solid can be

absorbed on inert material.

Evacuation Procedures

Large Spill Consider initial downwind evacuate for at least 300 meters (1000 feet).

Fire If tank, rail car or tank car is involved in a fire, isolate for 800 meters (1/2 mile) in all

directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions.

Reporting Requirements Spills that enter a water body must be reported immediately to the USEPA's

National Response Center at (800)424-8802. Check with your local and state

regulators regarding their reporting requirements.

7. HANDLING AND STORAGE

Handling Do not pressure, cut, weld, braze, solder, drill, grind, or expose such containers to heat,

flame, sparks, static electricity, or other sources of ignition; they may explode. See NFPA 30

and OSHA 1910.106 – flammable and combustible liquids.

Storage Store away from heat, sparks, open flame, or strong oxidizing agents in closed and properly

labeled containers. Empty containers retain product residue (liquid, and/or vapor) and can

be dangerous

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lubricant Base Oil	5 mg/m3 8 hour(s). Form:	5 mg/m3 8 hour(s). Form:	2,500 mg/m3
(Petroleum) Highly refined	Mist	Mist	
synthetic oils			
Detergent/Inhibitor System		5 mg/m3 8 hour(s). Form:	
Mixture		Mist	

Engineering Measures Additional area ventilation or local exhaust may be required to maintain air

concentrations below recommended limits.

Personal Protective Equipment

Eye/Face Protection Safety glasses or face shield where splashing is possible. Full face-shield to

be worn during emergencies.



SDS Number: 15005 Revision Date: June 24, 2024

Skin and Body As needed to prevent repeated skin contact. Solvent resistant gloves should

Protection be used if needed.

Respiratory Protection Not normally needed. During emergencies wear respirator.

Hygiene Measures Remove and wash contaminated clothing before re-use. Wash hands before

breaks and immediately after handling the product.

PHYSICAL AND CHEMICAL PROPERTIES

Clear light yellow liquid Odor Mild Petroleum Oder **Appearance**

Physical State Liquid Hq N/A

Flash Point >400 °F Autoignition >315°C /600°F

Temperature Freezing Point <-40°C **Boiling Point/Range** No data

Explosion Limits Flammability Limits in N/A N/A

Air **Specific Gravity** 0.86 - 0.88Solubility Negligible

Evaporation Rate Vapor Pressure < 0.01 N/A **Vapor Density** Not Determined Density N/A

10. STABILITY AND REACTIVITY

Stability STABLE under recommended storage conditions and room temperature.

Incompatible Products Open Flame and strong oxidizing agents.

Conditions to Avoid Heat, flames, and sparks.

Hazardous Decomposition Combustion products may include smoke, fumes, oxides of phosphorus,

Products boron, sulfur, nitrogen, carbon dioxide, carbon monoxide, and other low

molecular weight hydrocarbons.

Hazardous Polymerization None under normal processing.

11. TOXICOLOGICAL INFORMATION

THIS PRODUCT IS NON-HAZ FOR STORAGE AND TRANSPORTATION

Product Information Test on similar materials show a low order of acute oral and dermal toxicity.

Acute Oral **Effects**

Test on similar materials indicates low order of acute toxicity.

Acute Inhalation

Low acute toxicity expected on inhalation. **Effects**

Skin Effects Practically non-toxic if absorbed. Other similar highly refined products have not

shown skin tumors in mouse skin painting studies.

Eye Irritation Minimal irritation on contact. Eye irritation slightly or practically non-irritating base on

similar products.



SDS Number: 15005 Revision Date: June 24, 2024

Component Information

Chemical Name		LD50 Oral	LD50 Dermal	LC50 Inhalation		
	Lubricant Base Oil					
	(Petroleum) Highly refined	Not Available	Not Available	Not Available		
	synthetic oils (C15-C50)					

Chronic Toxicity

Chronic Toxicity Prolonged exposure may cause chronic effects. On rare occasions, prolonged and

repeated exposure to oil mist poses a risk of pulmonary disease such as chronic lung inflammation. This condition is usually asymptomatic as a result of repeated small

aspirations.

Carcinogenicity Not considered a potential carcinogen base on IP346 DMSO of less than 3.0 wt%

Target Organ Effects Respiratory system, Eyes, Skin,

Genotoxicity This product is considered non-mutagenic and has negative potential for tumor

development based on from Modified Ames Assay, with Mutagenic Index of less than

1.0.

12. ECOLOGICAL INFORMATION

Ecotoxicity If applied to leaves, this product may kill grasses and small plants by interfering with

transpiration and respiration. This product is not toxic to fish but may coat gill structures resulting in suffocation if spilled in shallow, running water. Product may be moderately toxic to amphibians by preventing dermal respiration. This product may cause gastrointestinal distress to birds and mammals through ingestion during

pelage grooming.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Microtox	Daphnia Magna (Water Flea)
Lubricant Base Oil (Petroleum) Highly refined SYNTHETIC base oils	Not Available	Not Available	Not Available	Not Available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method Dispose of in accordance with local regulations. Keep this product out of sewers

and waterways.

Contaminated Packaging Dispose of in accordance with local regulations.

14. TRANSPORT INFORMATION

DOT Not regulated

<u>IATA</u> Not regulated

IMDG/IMO Not regulated



SDS Number: 15005 Revision Date: June 24, 2024

15. REGULATORY INFORMATION

International Inventories

TSCA	DSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Х	Х	Χ	Χ	Х	Χ	Х	Χ

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health HazardNoChronic Health HazardNoFire HazardNoSudden Release of PressureNoHazard

Reactive Hazard No

Clean Water Act

If spilled into navigable waters it is reportable to National Response Center, 800-424-8802. Reportable Quantity = Oil Sheen present on navigable water surface. (40 CFR 116; 401.15)

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CERCLA

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

Florida

No listed ingredients are present

Massachusetts RTK

No listed ingredients are present

Minnesota RTK

No listed ingredients are present

New Jersey RTK

Lists petroleum oil, but this product does not contain hazardous ingredients.

Pennsylvania RTK

Lists petroleum oil, but this product does not contain hazardous ingredients greater than 3%.

Illinois DOL TSL

No listed ingredients are present

International Regulations

Mexico – Grade No information available.

Canada Not listed on the Canadian Controlled Product Ingredient Disclosure and is compliant

with Controlled Products Regulation



SDS Number: 15005 Revision Date: June 24, 2024

CONEG Metals Since cadmium, chromium, lead, and mercury are not detectable and it does not exceed

100ppm total in this product, it is compliant with CONEG Metals regulation.

EEC (Europe) This product is not known to be a dangerous good internationally.

R-Phrases R45: May Cause Cancer

S-Phrases S53: Avoid exposure - obtain special instructions before use.

S45: In case of accident or if you feel unwell, seek medical advice

immediately (show the label where possible).

Hazard Label None Danger Symbol None

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

16. OTHER INFORMATION

Prepared By TRIAX, LLC

Revision Date June 24, 2024

Revision Note None

Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End MSDS