

NFPA	HMIS			
1	Health Hazard	0		
	Fire Hazard	1		
< Y	Reactivity	0		

This SDS Is in accordance with US 2012 OSHA Hazard Communication Standard (29 CFR1910.1200) or the Canadian Workplace Hazardous Material Information System (WHMIS 2015)

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name	TRIAX CVT ATF
Recommended Use	Automatic continuously variable transmission Not for use in internal combustion engines
Manufactured by:	TRIAX LLC 751 Port America, Suite 810. Grapevine, TX 76051 Phone: 214-897-6533
Emergency Telephone Number	CHEMTREC 1 (800) 424-9300 International: +011(703) 527-3887

2. HAZARDS IDENTIFICATION

Emergency Overview

Classification

This product is **not considered hazardous** by either the US 2012 OSHA Hazard Communication Standard (29 CFR1910.1200) or the Canadian Workplace Hazardous Material Information System (WHMIS 2015.

Appearance	Green liquid	Physical State	liquid	Odor	Petroleum odor
Potential Heal	th Effects				
Acute Toxicity Eyes Skin Inhalati Ingestie		No significant effects No significant effects No significant effects No significant effects	or critical hazards. or critical hazards.		
Environmental	Hazard	See Section 12 for ac	ditional Ecological Inform	ation.	
Other hazards		None known			



3. COMPOSITION / INFORMATION ON INGREDIENTS

 Formula
 Mixture

 Chemical Name
 CAS-No
 Weight %

 Lubricant Base Oil (Petroleum) Highly refined synthetic oils
 Mixture
 80-95%

 Automatic Transmission Oil Additive Mixture
 Proprietary and Confidential*
 5-20%

This product does not contain known hazardous materials at the $\geq 1\%$ level or known carcinogens at the $\geq 0.1\%$ level as defined by 29 CFR 1910.1200.

* Exact % of composition is being withheld as a trade secret.

	4. FIRST-AID MEASURES
Eye Contact	Flush with large amounts of water for 15 minutes.
Skin Contact	Wash off immediately with soap and plenty of water for at least 15 minutes while removing all contaminated clothing and shoes.
Inhalation	This material is not expected to present an inhalation exposure at ambient conditions.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Get immediate medical attention or advice.
Notes to Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flamma	ole Properties					NOT	FLAN	MMABLE
Flash Po	pint					>400	°F	
Suitable	Extinguishing M	edia				Wate	r fog,	Foam, CO ₂ , dry chemical
Unsuitable Extinguishing Media		Not Available						
Hazardo	us Combustion F	Produ	icts			Not Available		
	o <u>n Data</u> Sensitivity to Me Sensitivity to Sta					Not s Not s		
Protective Equipment and Precautions for Firefighters		Wear positive pressure self-contained breathing apparatus (SCBA). Use water to cool containers exposed to flames. Structural firefighters' protective clothing will only provide limited protection. Mist or sprays may be flammable below the product normal flash point.		(SCBA). Use water to cool containers o flames. Structural firefighters' protective Il only provide limited protection. Mist or y be flammable below the product normal				
<u></u>	Health Hazard	0	Flammability	1	Stab	ility	0	Physical and Chemical - Hazards



6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Use personal protective equipment. Avoid contact with skin, eyes, and clothing. Ensure adequate ventilation. If spilled, take caution, as material can cause surfaces to become very slippery.
Methods for Containment	Dike far ahead of liquid spill for later disposal.
Methods for Cleaning Up	Pick up free liquid for recycle and/or disposal. Residual liquid and/or solid can be absorbed on inert material.
Evacuation Procedures Large Spill Fire	Consider initial downwind evacuate for at least 300 meters (1000 feet). If tank, rail car or tank car is involved in a fire, isolate for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions.
Reporting Requirements	Spills that enter a water body must be reported immediately to the USEPA's National Response Center at (800)424-8802. Check with your local and state regulators regarding their reporting requirements.
	7. HANDLING AND STORAGE

Handling	Do not pressure, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode. See NFPA 30 and OSHA 1910.106 – flammable and combustible liquids.
Storage	Store away from heat, sparks, open flame, or strong oxidizing agents in closed and properly labeled containers. Empty containers retain product residue (liquid, and/or vapor) and can be dangerous

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lubricant Base Oil	5 mg/m3 8 hour(s). Form:	5 mg/m3 8 hour(s). Form:	2,500 mg/m3
(Petroleum) Highly refined	Mist	Mist	
synthetic oils			
Detergent/Inhibitor System		5 mg/m3 8 hour(s). Form:	
Mixture		Mist	

Engineering Measures	Additional area ventilation or local exhaust may be required to maintain air concentrations below recommended limits.
Personal Protective Equipment	
Eye/Face Protection Skin and Body	Safety glasses or face shield where splashing is possible. Full face-shield to be worn during emergencies. As needed to prevent repeated skin contact. Solvent resistant gloves should
Protection Respiratory Protection	be used if needed. Not normally needed. During emergencies wear respirator.
Hygiene Measures	Remove and wash contaminated clothing before re-use. Wash hands before breaks and immediately after handling the product.



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Physical State Flash Point	Green liquid Liquid >400 °F	Odor pH Autoignition Temperature	Mild Petroleum Odor N/A >315°C /600°F
Boiling Point/Range Explosion Limits	No data N/A	Freezing Point Flammability Limits in Air	<-40°C/°F N/A
Specific Gravity Evaporation Rate Vapor Density	0.86 – 0.88 N/A Not Determined	Solubility Vapor Pressure Density	Negligible <0.01 N/A
	10.	STABILITY AND REACTIVITY	
Stability STABLE under recommended storage conditions and room temperature.			
Incompatible Produc	Incompatible Products Open Flame and strong oxidizing agents.		
Conditions to Avoid Heat, flames, and sparks.			

Hazardous Decomposition
ProductsCombustion products may include smoke, fumes, oxides of phosphorus,
boron, sulfur, nitrogen, carbon dioxide, carbon monoxide, and other low
molecular weight hydrocarbons.

Hazardous Polymerization None under normal processing.

11. TOXICOLOGICAL INFORMATION

THIS PRODUCT IS NON-HAZ FOR STORAGE AND TRANSPORTATION

Product Information	Test on similar materials show a low order of acute oral and dermal toxicity.
Acute Oral Effects	Test on similar materials indicates low order of acute toxicity.
Acute Inhalation Effects	Low acute toxicity expected on inhalation.
Skin Effects	Practically non-toxic if absorbed. Other similar highly refined products have not shown skin tumors in mouse skin painting studies.
Eye Irritation	Minimal irritation on contact. Eye irritation slightly or practically non-irritating base on similar products.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Lubricant Base Oil (Petroleum) Highly refined synthetic oils mixture	Not Available	Not Available	Not Available

Chronic Toxicity

Chronic Toxicity

Prolonged exposure may cause chronic effects. On rare occasions, prolonged and repeated exposure to oil mist poses a risk of pulmonary disease such as chronic lung inflammation. This condition is usually asymptomatic as a result of repeated small aspirations.



Carcinogenicity	Not considered a potential carcinogen base on IP346 DMSO of less than 3.0 wt%
Target Organ Effects	Respiratory system, Eyes, Skin,
Genotoxicity	This product is considered non-mutagenic and has negative potential for tumor development based on from Modified Ames Assay, with Mutagenic Index of less than 1.0.

12. ECOLOGICAL INFORMATION

Ecotoxicity If applied to leaves, this product may kill grasses and small plants by interfering with transpiration and respiration. This product is not toxic to fish but may coat gill structures resulting in suffocation if spilled in shallow, running water. Product may be moderately toxic to amphibians by preventing dermal respiration. This product may cause gastrointestinal distress to birds and mammals through ingestion during pelage grooming.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Microtox	Daphnia Magna (Water Flea)
Lubricant Base Oil (Petroleum) Highly refined synthetic Oils mixture	Not Available	Not Available	Not Available	Not Available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method	Dispose of in accordance with local regulations. Keep this product out of sewers and waterways.
Contaminated Packaging	Dispose of in accordance with local regulations.

14. TRANSPORT INFORMATION

DOT Not regulated

IATA Not regulated

IMDG/IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	DSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Х	Х	Х	Х	Х	Х	Х	Х

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.



SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure	No
Hazard	
Reactive Hazard	No

Clean Water Act

If spilled into navigable waters it is reportable to National Response Center, 800-424-8802. Reportable Quantity = Oil Sheen present on navigable water surface. (40 CFR 116; 401.15)

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CERCLA

U.S. State Regulations

California Proposition 65 This product does not contain any Proposition 65 chemicals. Florida No listed ingredients are present Massachusetts RTK No listed ingredients are present Minnesota RTK No listed ingredients are present New Jersey RTK Lists petroleum oil, but this product does not contain hazardous ingredients. Pennsylvania RTK Lists petroleum oil, but this product does not contain hazardous ingredients greater than 3%. Illinois DOL TSL No listed ingredients are present

International Regulations

Mexico – Grade	No information available.		
Canada	Not listed on the Canadian Controlled Product Ingredient Disclosure and is compliant with Controlled Products Regulation		
CONEG Metals	Since cadmium, chromium, lead, and mercury are not detectable and it does not exceed 100ppm total in this product, it is compliant with CONEG Metals regulation.		
EEC (Europe)	This product is not kno R-Phrases S-Phrases Hazard Label Danger Symbol	own to be a dangerous good internationally. R45: May Cause Cancer S53: Avoid exposure - obtain special instructions before use. S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). None None	

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.



16. OTHER INFORMATION

Prepared By TRIAX, LLC

Revision Date June 24, 2024

Revision Note None

Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End MSDS