



# TRIAX HYDRO-BOOST

## FULL SYNTHETIC HYDRAULIC OIL BOOSTER & STOP LEAK

TRIAX Hydro-Boost is a hydraulic system treatment, booster and stop leak designed to optimize hydraulic fluid functionality, eliminate or minimize leaks, noise and fluid performance in a wide range of hydraulic applications. It contains advanced synthetic chemistry for metal protection, seal restorer, anti-wear and viscosity stability.

### PERFORMANCE

- Protects Pumps, Seals, Motors and other hydraulic system components.
- Revitalizes Seals & O-Rings.
- Extends hydraulic oil life by up to 300%, stabilizing oxidation rates, viscosity shear and replenishing oil additives
- Prevents small to medium leaks caused by worn pistons and seals. Helps optimize oil flow and pump functionality.
- Contains defoamers and anti-wear agents, preventing foaming, wear and oil degradation and hydraulic cavitation in high temp operation.
- ONLY 3% treat rate: 1 gallon treats 33 gallons of hydraulic oil.

### APPLICATIONS

- Construction Equipment
- Farming Equipment
- Hydraulic Lifts
- Earth Movers/Loaders
- Forklifts & Hydraulic Jacks
- Dump trucks
- Cranes & Industrial Equipment
- Logging Equipment

### HOW TO USE

**PREVENTIVE:  
1.5% BY VOLUME**

**NORMAL USE:  
3% BY VOLUME**

**HIGH WEAR:  
6% BY VOLUME**

This product does NOT repair ruptured seals, it repairs cracked or moderately worn seals.

If the fluid leak does not stop, piston / fitting seals will need to be replaced.

DO NOT USE IN ENGINES OR TRANSMISSIONS

### CHEMICAL PROPERTIES

Specific Gravity @ 60F	0.828
Viscosity @ 100°C, cSt, ASTM D445	7.3
Viscosity @ 40°C, cSt, ASTM D445	44
Viscosity Index, ASTM D2270	120
Pour Point, °C, ASTM D97	-35
Flash Point, °C(F), ASTM D92	220 (430)

**COMPATIBLE WITH ALL TYPES OF  
HYDRAULIC OIL: ISO 32, ISO 46, ISO 68**

**1 GAL TREATS  
33 GAL OF OIL**