

TRIAX MAX OIL BOOSTER S7

FRICITION MODIFIER, OIL BOOSTER & ENGINE CLEANER

TRIAX Max Oil Booster S7 is one of the most advanced engine oil supplements and engine treatments ever made with an extremely wide range of benefits, in virtually every aspect of engine and oil functionality. It is basically an engine treatment on steroids, as well as sludge and carbon deposit cleaner, anti-wear friction modifier, oil viscosity stabilizer, TBN booster, acid neutralizer and corrosion preventer - ALL IN ONE product.

TRIAX Max Oil Booster S7 is the best engine protector and oil booster you can buy, from any brand anywhere in the world. It contains a patented, proprietary formulation of ultra-high performance additives and inhibitors to bring you the most advanced engine protection possible.

PERFORMANCE

- Friction reduction & massive anti-wear boost with boron, organic molybdenum and zinc.
- Rapidly cleans carbon deposits from pistons rings, turbo-charges, and other critical engine parts.
- Boost TBN by up to 6 points for 10 quarts treat.
- Replenishes oil additives and extends drain intervals.
- Frees stuck piston rings and oil pressurized injectors.
- Significantly reduces oil oxidation.
- Faster starts, rapid turbo spooling and a quieter engine.

PERFORMANCE HIGHLIGHTS

VISCOSITY
STABILITY

TBN
BOOST

ENGINE SLUDGE
CLEANER

ENGINE OIL LIFE
EXTENDER

TURBO-CHARGER
PROTECTION

OXIDATION
STABILITY

COMPLETE
COMPATIBILITY

APPLICATIONS

TRIAX MAX OIL BOOSTER S7 is recommended for use in both heavy duty and passenger engine oils to push engine oil capabilities far beyond original specifications.

Use with ALL motor oils. Mineral, synthetic-blends, full synthetics. Can be used with heavy duty equipment, trucks, pickups, SUV's, racing vehicles and passenger cars.

HOW TO USE

NORMAL USE - 1 BOTTLE FOR 10 QUARTS ENGINE OIL
FIRST USE (ENGINE CLEANING) - 1 BOTTLE FOR 5 QUARTS ENGINE OIL

CHEMICAL PROPERTIES

Specific Gravity @ 60F	0.95
Viscosity @ 100°C, cSt, ASTM D445	14
Viscosity @ 40°C, cSt, ASTM D445	90
Viscosity Index, ASTM D2270	110
Flash Point, °C(F), ASTM D92	90 (194)
Color, ASTM D1500	4.5

ONLY USE IN ENGINE OIL!

DO NOT OVERFILL CRANKCASE! For sludge cleaning, add TRIAX S7 to engine oil 1,500 miles before oil change. When oil change is reached, change the oil and add TRIAX S7 Oil Booster for continued protection.