

# TRIAX OEM GRADE PSF

## FULL SYNTHETIC POWER STEERING FLUID

TRIAX OEM GRADE Power Steering Fluid (PSF) is a universal, ultra-high-performance power steering fluid designed to meet a wide range of automotive power steering system requirements. Our unique, custom built formula is designed to surpass OEM requirements for high performance hydraulic power steering pumps, servos and power steering response and protection. This product is blended with top tier full synthetic high grade base oils and contains customized additive system to guarantee compliance with a large spectrum of automotive steering systems offering exceptional low temperature fluidity, outstanding power steering response and complete protection for all seals / gaskets made from either synthetic or natural materials.

TRIAX OEM GRADE PSF is designed as a service complete fill as well as top off fluid. It can be mixed almost any existing ATF in the power steering systems without damaging it or degrading performance.

## PERFORMANCE HIGHLIGHTS

- Extremely wide compatibility range
- Recommended for complete refill or topping off
- Exceptional seal protection and durability
- LIFETIME FILL unless OEM time / miles requirements
- Excellent durability under severe driving conditions
- Superior functionality at both low and high temperatures
- Excellent high temp operational performance
- Prevents “squishy” or “lazy” steering
- Protects pumps and bearings from corrosion and wear

## APPLICATIONS & SPECIFICATIONS

European, Asian and US modern vehicle

FILL FOR LIFE - this fluid is designed not to be changed unless OEM specifies drain interval on the vehicle.

**USE IN POWER STEERING SYSTEM ONLY!** This product can also be used in any vehicle which requires an ATF Dexron III or ATF +4 fluid in power steering systems.

- Audi P/N G002000
- BMW
- Chrysler MS 1872
- Chrysler MS 5931F P/N 04883077
- Chrysler MS 9602, ATF+4
- Ford M2C128-C and D
- Ford M2C138-CJ, Ford M2C33-F
- GM 9985010 Saginaw PSF System
- GM 9985835 Wide Temp Performance
- GM P/N 89021184
- Hyundai / Kia PSF-3 & PSF-4
- Hyundai PSF-3
- Kia PSF-3
- Mercedes Benz 236.3 P/N 000 989 8803
- Mitsubishi Diamond SP III
- Mitsubishi PS Fluid
- Nissan PSF-II
- Pentosin CHF 7.1
- Subaru P/N K0209A0080
- Toyota PSF type EH, P/N 008886-01
- VW P/N G002000
- Where ATF Dex III is required

If a specification is listed above, TRIAX LLC guarantees the product meets, exceeds that specification or is safe to use in equipment requiring that application, and is therefore covered by our product warranty.

## CHEMICAL PROPERTIES

Specific Gravity @ 60F	0.828
Viscosity @ 100°C, cSt, ASTM D445	6.98
Viscosity @ 40°C, cSt, ASTM D445	32.61
Viscosity Index, ASTM D2270	180
Pour Point, °C, ASTM D97	-54
Flash Point, °C(F), ASTM D92	220 (428)

Small deviations from these results are expected during the manufacturing process and do not affect product performance or specification compliance.

All trademarked names are the property of their respective owners and may be registered marks in some countries. No affiliation or endorsement claim, express or implied, is made by their use, which is strictly to guide consumers as to the application of TRIAX products and convey compatibility or lack thereof.