

| NFPA | HMIS | | | |
|------|---------------|---|--|--|
| | Health Hazard | 0 | | |
| | Fire Hazard | 1 | | |
| X X | Reactivity | 0 | | |

This SDS Is in accordance with US 2012 OSHA Hazard Communication Standard (29 CFR1910.1200) or the Canadian Workplace Hazardous Material Information System (WHMIS 2015)

1. PRODUCT AND COMPANY IDENTIFICATION

| Product Name | TRIAX Synergy Gear HD 30W, 40W, 50W |
|----------------------------|---|
| Recommended Use | Transmission, Gear and Differential, GL-5, Limited Slip Included Not for use in internal combustion engines |
| Manufactured by: | TRIAX LLC 751 Port America, Suite 810. Grapevine, TX 76051 Phone: 214-897-6533 |
| Emergency Telephone Number | CHEMTREC 1 (800) 424-9300 International: +011(703) 527-3887 |

2. HAZARDS IDENTIFICATION

Emergency Overview

Classification

This product is **not considered hazardous** by either the US 2012 OSHA Hazard Communication Standard (29 CFR1910.1200) or the Canadian Workplace Hazardous Material Information System (WHMIS 2015.

| Appearance | Clear light yellow liquid | Physical State | liquid | Odor | Petroleum odor |
|---|------------------------------|--|--|--------|----------------|
| Potential Healt | h Effects | | | | |
| Acute Toxicity Eyes Skin Inhalatic Ingestio | | No significant effects No significant effects No significant effects No significant effects | or critical hazards. or critical hazards. | | |
| Environmental H | lazard | See Section 12 for ad | ditional Ecological Inform | ation. | |
| Other hazards | | None known | | | |
| | | | | | |



3. COMPOSITION / INFORMATION ON INGREDIENTS

| Formula Mixture | | |
|--|-------------------------------|----------|
| Chemical Name | CAS-No | Weight % |
| Lubricant Base Oil (Petroleum) Highly refined synthetic oils (C15-C50) | Mixture | 90-99.9% |
| Transmission / Gear Oil Additive Mixture | Proprietary and Confidential* | 0.1-10% |

This product does not contain known hazardous materials at the \geq 1% level or known carcinogens at the \geq 0.1% level as defined by 29 CFR 1910.1200.

* Exact % of composition is being withheld as a trade secret.

| | 4. FIRST-AID MEASURES |
|--------------------|--|
| Eye Contact | Flush with large amounts of water for 15 minutes. |
| Skin Contact | Wash off immediately with soap and plenty of water for at least 15 minutes while removing all contaminated clothing and shoes. |
| Inhalation | This material is not expected to present an inhalation exposure at ambient conditions. |
| Ingestion | Never give anything by mouth to an unconscious person. Do not induce vomiting. Get immediate medical attention or advice. |
| Notes to Physician | Treat symptomatically. |

5. FIRE-FIGHTING MEASURES

| Flammable Properties | | | NOT FLAMMABLE | | | | | |
|---|-------------------|-------|---|--------------------------------|---|---------------|---|------------------------------------|
| Flash Point | | | >400 | °F | | | | |
| Suitable Extinguishing Media | | | Water fog, Foam, CO ₂ , dry chemical | | | | | |
| Unsuita | ble Extinguishing | y Mec | lia | | | Not Available | | |
| Hazardous Combustion Products | | | Not Available | | | | | |
| Explosion Data Sensitivity to Mechanical Impact Sensitivity to Static Discharge | | | | Not sensitive Not sensitive | | | | |
| Protective Equipment and Precautions for Firefighters | | | Wear positive pressure self-contained breathing apparatus (SCBA). Use water to cool containers exposed to flames. Structural firefighters' protective clothing will only provide limited protection. Mist or sprays may be flammable below the product normal flash point. | | (SCBA). Use water to cool containers o flames. Structural firefighters' protective Il only provide limited protection. Mist or y be flammable below the product normal | | | |
| <u>NFPA</u> | Health Hazard | 0 | Flammability | 1 | Stab | oility | 0 | Physical and Chemical - Hazards |



6. ACCIDENTAL RELEASE MEASURES

| Personal Precautions | Use personal protective equipment. Avoid contact with skin, eyes, and clothing. Ensure adequate ventilation. If spilled, take caution, as material can cause surfaces to become very slippery. |
|--|---|
| Methods for Containment | Dike far ahead of liquid spill for later disposal. |
| Methods for Cleaning Up | Pick up free liquid for recycle and/or disposal. Residual liquid and/or solid can be absorbed on inert material. |
| Evacuation Procedures Large Spill Fire | Consider initial downwind evacuate for at least 300 meters (1000 feet). If tank, rail car or tank car is involved in a fire, isolate for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. |
| Reporting Requirements | Spills that enter a water body must be reported immediately to the USEPA's National Response Center at (800)424-8802. Check with your local and state regulators regarding their reporting requirements. |
| | 7. HANDLING AND STORAGE |

| Handling | Do not pressure, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode. See NFPA 30 and OSHA 1910.106 – flammable and combustible liquids. |
|----------|---|
| Storage | Store away from heat, sparks, open flame, or strong oxidizing agents in closed and properly labeled containers. Empty containers retain product residue (liquid, and/or vapor) and can be dangerous |

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|----------------------------|--------------------------|--------------------------|-------------|
| Lubricant Base Oil | 5 mg/m3 8 hour(s). Form: | 5 mg/m3 8 hour(s). Form: | 2,500 mg/m3 |
| (Petroleum) Highly refined | Mist | Mist | |
| synthetic oils | | | |
| Detergent/Inhibitor System | | 5 mg/m3 8 hour(s). Form: | |
| Mixture | | Mist | |

| Engineering Measures | Additional area ventilation or local exhaust may be required to maintain air concentrations below recommended limits. |
|-------------------------------|---|
| Personal Protective Equipment | |
| Eye/Face Protection | Safety glasses or face shield where splashing is possible. Full face-shield to be worn during emergencies. |
| Skin and Body Protection | As needed to prevent repeated skin contact. Solvent resistant gloves should be used if needed. |
| Respiratory Protection | Not normally needed. During emergencies wear respirator. |
| Hygiene Measures | Remove and wash contaminated clothing before re-use. Wash hands before breaks and immediately after handling the product. |



9. PHYSICAL AND CHEMICAL PROPERTIES

| Appearance Physical State Flash Point | Clear light yellov Liquid >400 °F | w liquid | Odor pH Autoignition | Mild Petroleum Odor N/A >315°C /600°F |
|---|---|-------------------------------|---|---|
| Boiling Point/Range Explosion Limits | No data N/A | | Temperature Freezing Point Flammability Limits in Air | <-40°C N/A |
| Specific Gravity Evaporation Rate Vapor Density | 0.86 – 0.88 N/A Not Determined | | Solubility Vapor Pressure Density | Negligible <0.01 N/A |
| 10. STABILITY AND REACTIVITY | | | | |
| Stability | | STABLE under r | ecommended storage condit | ions and room temperature. |
| Incompatible Product | ts | Open Flame and | strong oxidizing agents. | |
| Conditions to Avoid | | Heat, flames, and sparks. | | |
| Hazardous Decompo Products | sition | | ducts may include smoke, fui rogen, carbon dioxide, carbo t hydrocarbons. | · · · · |
| Hazardous Polymeriz | ation | None under normal processing. | | |

11. TOXICOLOGICAL INFORMATION

THIS PRODUCT IS NON-HAZ FOR STORAGE AND TRANSPORTATION

| Product Information | Test on similar materials show a low order of acute oral and dermal toxicity. |
|-----------------------------|---|
| Acute Oral Effects | Test on similar materials indicates low order of acute toxicity. |
| Acute Inhalation Effects | Low acute toxicity expected on inhalation. |
| Skin Effects | Practically non-toxic if absorbed. Other similar highly refined products have not shown skin tumors in mouse skin painting studies. |
| Eye Irritation | Minimal irritation on contact. Eye irritation slightly or practically non-irritating base on similar products. |

Component Information

| Chemical Name | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|--|---------------|---------------|-----------------|
| Lubricant Base Oil (Petroleum) Highly refined synthetic oils | Not Available | Not Available | Not Available |

Chronic Toxicity

| Chronic Toxicity | Prolonged exposure may cause chronic effects. On rare occasions, prolonged and repeated exposure to oil mist poses a risk of pulmonary disease such as chronic lung inflammation. This condition is usually asymptomatic as a result of repeated small aspirations. |
|------------------|---|
| Carcinogenicity | Not considered a potential carcinogen base on IP346 DMSO of less than 3.0 wt $\%$ |



Target Organ EffectsRespiratory system, Eyes, Skin,GenotoxicityThis product is considered non-mutagenic and has negative potential for tumor
development based on from Modified Ames Assay, with Mutagenic Index of less than
1.0.

12. ECOLOGICAL INFORMATION

Ecotoxicity

If applied to leaves, this product may kill grasses and small plants by interfering with transpiration and respiration. This product is not toxic to fish but may coat gill structures resulting in suffocation if spilled in shallow, running water. Product may be moderately toxic to amphibians by preventing dermal respiration. This product may cause gastrointestinal distress to birds and mammals through ingestion during pelage grooming.

| Chemical Name | Toxicity to Algae | Toxicity to Fish | Microtox | Daphnia Magna (Water Flea) | |
|--|---|------------------|---------------|-------------------------------|--|
| Lubricant Base Oil (Petroleum) Highly refined synthetic base oils | etroleum) Highly Not Available Not synthetic base | | Not Available | Not Available | |

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method Dispose of in accordance with local regulations. Keep this product out of sewers and waterways.

Contaminated Packaging Dispose of in accordance with local regulations.

14. TRANSPORT INFORMATION

DOT Not regulated

IATA Not regulated

IMDG/IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

| TSCA | DSL | EINECS/ELINCS | ENCS | IECSC | KECL | PICCS | AICS |
|------|-----|---------------|------|-------|------|-------|------|
| Х | Х | Х | Х | Х | Х | Х | Х |

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.



SARA 311/312 Hazard Categories

| Acute Health Hazard | No |
|----------------------------|----|
| Chronic Health Hazard | No |
| Fire Hazard | No |
| Sudden Release of Pressure | No |
| Hazard | |
| Reactive Hazard | No |

Clean Water Act

If spilled into navigable waters it is reportable to National Response Center, 800-424-8802. Reportable Quantity = Oil Sheen present on navigable water surface. (40 CFR 116; 401.15)

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CERCLA

U.S. State Regulations

California Proposition 65 This product does not contain any Proposition 65 chemicals. Florida No listed ingredients are present Massachusetts RTK No listed ingredients are present Minnesota RTK No listed ingredients are present New Jersey RTK Lists petroleum oil, but this product does not contain hazardous ingredients. Pennsylvania RTK Lists petroleum oil, but this product does not contain hazardous ingredients greater than 3%. Illinois DOL TSL No listed ingredients are present

International Regulations

| Mexico - Grade | No information available. | | | | | |
|----------------|--|--|--|--|--|--|
| Canada | Not listed on the Canadian Controlled Product Ingredient Disclosure and is compliant with Controlled Products Regulation | | | | | |
| CONEG Metals | Since cadmium, chromium, lead, and mercury are not detectable and it does not exceed 100ppm total in this product, it is compliant with CONEG Metals regulation. | | | | | |
| EEC (Europe) | This product is not kno R-Phrases S-Phrases Hazard Label Danger Symbol | own to be a dangerous good internationally. R45: May Cause Cancer S53: Avoid exposure - obtain special instructions before use. S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). None None | | | | |

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.



16. OTHER INFORMATION

Prepared By TRIAX, LLC

Revision Date June 24, 2024

Revision Note None

Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End MSDS